

We speak carpet tile!



MIFLOR

We speak carpet tile!



Start with  
PROJECT  
FLOORS.....  
and lead  
a more creative,  
productive life.






 Dune 5+8



MOOIFLOR

Dune 2 



Ecover



clean air



Dune 1+4

May time be gentle,  
may time never be wasted,  
and may all your luck  
come by chance.



Dune 1+3



Creativity  
is more than  
just being  
different.  
Making  
the simple,  
awesomely  
simple,  
that's  
creativity.



**PROJECTFLOORS**



Dune 5+6



# Thrive<sup>®</sup> matter

THRIVE<sup>®</sup> MATTER World's first carbon negative fibre

- 100% post-industrial recycled resin- for a total of 90% recycled content
- 100% Recyclable
- High bulk, lightweight coverage
- 100% solution-dyed color, Average MR<2.0



Carbonfund.org



GreenCircle  
Independent GreenCircle<sup>®</sup> Certification



LCA, UL<sup>®</sup>EPD  
Life Cycle Assessment(LCA),  
Third-Party Certified Environmental  
Product Declaration



C2C Certified Material Health Certificate<sup>™</sup>  
GOLD LEVEL



Adding value to projects in varying  
Green Rating Systems



# PROJECT FLOORS

Your Project. Our Floors.

## DUNE SERIES



Dune 1



Dune 2




Dune 3



Dune 4



Dune 5



Dune 6




Dune 7



Dune 8



## INSTALLATION METHODS



Style Name:	Dune
Construction:	Multi-level loop
Yarn:	Universal Thrive <sup>®</sup> matter Nylon6
Color System:	100% Solution Dyed
Gauge:	1/10
Stitches:	8 per inch
Pile Weight:	23 oz/yd <sup>2</sup>
Pile Height:	4.5mm-7.5 mm (±0.5mm) UltraEco Pro
Backing:	60cm×60cm
Area of Use:	Heavy Commercial
Flammability:	Passes (ASTM E 648-17) Class I Passes (GB 8624-2012) B1
Smoke Density:	Passes ASTM E 662 Less than 450
Static Propensity:	Passes AATCC-134≤3.5kV
Static Control:	Life-of-the carpet Static Protection
Formaldehyde Purification:	Passes (JC/T 1074-2008) Class I