

Vinyl Wall Covering Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS

HIGH PERFORMANCE VINYL WALL COVERINGS FOR COMMERCIAL APPLICATION

ITEM	RESULT	STANDARD
Overall thickness	1.0mm	EN 428
Wear layer thickness	0.10mm	EN 429
Weight	800g	EN 430
Dimensional Stability	0.06%	EN 434
Abrasion resistance (test cycle)	Above 15000 cycle	EN 425
Colourfastness	Min 6 degree	ISO 105-B02
Fire resistance	B1 Class	ISO 4102
Static Electricity	Pass	En 1081/IEC 1340-1
Stain resistance	Excellent	En 423
Flexability	Excellent	EN 435
Recommended Usage Wall covering is fully impact resistant and is therefore ideal for use as a cladding in large public buildings such as hospitals, care institutions, surgeries, clean rooms, stores, and supermarkets, warehouse areas.	Installation Installation should be carried out in accordance with local standards. All surfaces are to be primed with an appropriate primer and allowed to dry overnight prior to the application of the vinyl sheet. The material must be allowed to acclimatise 24 hours before installation in a room temperature of between 18-24°C.	Maintenance Maintenance should be carried out regularly to retain the appearance and durability of the wall covering. Mural club should be maintained using a fine grade abrasive and a neutral cleanser.

