

Thrive[®] matter

THRIVE[®] MATTER World's first carbon negative fibre

- 100% post-industrial recycled resin-for a total of 90% recycled content
- High bulk, lightweight coverage
- 100% Recyclable
- 2.0 100% solution-dyed color, Average MR<2.0



Carbonfund.org



GreenCircle[®]
Independent GreenCircle[®] Certification



LCA, UL[®]EPD
Life Cycle Assessment(LCA),
Third-Party Certified Environmental
Product Declaration



Version 4.0
C2C Certified Material Health Certificate[™]
GOLD LEVEL


Adding value to projects in varying
Green Rating Systems




BARRYS POINT COLLECTION



Barrys Point #1



Barrys Point #2



Barrys Point #3



Barrys Point #4

INSTALLATION METHODS



Quarter Turn



Ashlar



Monolithic



Brick



Style Name:	BARRYS POINT
Construction:	Multi-level loop
Yarn:	Universal Thrive [®] matter Nylon6
Color System:	100% Solution Dyed
Gauge:	1/10
Stitches:	8 per inch
Pile Weight:	23 oz/yd ²
Pile Height:	4.5mm-7.5 mm (±0.5mm)
Backing:	EcoTX
Tile Size:	50cm×50cm
Area of Use:	Heavy Commercial
Flammability:	Passes (ASTM E 648-17) Class I Passes (GB 8624-2012) B ₁ Passes ASTM E 662 Less than 450 Passes AATCC-134≤3.5kV Life-of-the carpet Static Protection Passes (JC/T 1074-2008) Class I
Smoke Density:	
Static Propensity:	Static
Control:	Formaldehyde
Purification:	