

PROJECT FLOORS + Protile



PROJECT FLOORS (NZ) LTD SPECIFICATION



NEWMARKET

Specification	Details
Construction	Multi-level loop
Pile Height	2.5mm-5.0mm ($\pm 0.5\text{mm}$)
Yarn	100% Solution Dyed Nylon
Backing	Eurobac & EcoTX
Colour System	100% Solution Dyed
Tile Size	500 x 500 mm (5m ² /box)
Gauge	1/10
Total Height	5.5mm ($\pm 0.5\text{mm}$) / 8.5mm ($\pm 0.5\text{mm}$)
Stitches	12 per inch
Pile Weight	16oz
Total Weight	Eurobac & EcoTX: (3200 ± 100)g/m ² / (4200 ± 100)g/m ²
Recommended Adhesive	Specially formulated ProjectStik
Warranty	15 Year Product Warranty

Reaction-to-Fire Performance Compliance

Area of Building	Buildings not protected with an automatic fire sprinkler system	Building protected with an automatic fire sprinkler system	Complies?
Sleeping areas and exit ways in buildings with care/detention provided	4.5 kW/m ²	2.2 kW/m ²	✓ 8.6 kW/m ²
Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²	✓ 8.6 kW/m ²
Fire cells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²	✓ 8.6 kW/m ²
Exitways in all other buildings	1.2 kW/m ²	1.2 kW/m ²	✓ 8.6 kW/m ²

Approved Installation Methods



PROJECT FLOORS (NZ) Limited

55 Barrys Point Road, Takapuna 0622, Auckland

www.projectfloors.co.nz | 09 4444 165