



Velura

A twelve-tone multi-level loop carpet tile collection

Softly mottled A tones and more directional B tones create a coordinated system for calm fields, transitions and graphic zoning. Built for heavy commercial interiors in a compact 50 cm modular format.

12

COLOURWAYS

UltraEco

BACKING

100%

SOLUTION DYED

Class I

ASTM E648

THE COLOURWAYS



A-1



A-2



A-3



A-4



A-5



A-6



B-1



B-2




B-3



B-4



B-5



B-6

Layered by light

Velura combines multi-level loop construction with two coordinated tonal families. Universal Nylon 6 and Plencolor Nylon 6 are solution dyed for consistent colour, while UltraEco backing supports a stable modular installation under sustained commercial use.

SPECIFICATION

CONSTRUCTION

Multi-level loop

YARN

Universal Nylon 6 & Plencolor Nylon 6

COLOUR SYSTEM

100% solution dyed

GAUGE

1/12

STITCHES

10 per inch

PILE WEIGHT

17 oz/yd²

PILE HEIGHT

2.5-5.5 mm (+/- 0.5 mm)

BACKING

UltraEco

TILE SIZE

50 cm x 50 cm

TOTAL THICKNESS

6.0 mm (+/- 0.5 mm)

TOTAL WEIGHT

3200 (+/- 100) g/m²

AREA OF USE

Heavy commercial

FLAMMABILITY

Passes ASTM E648-17 Class I
Passes GB 8624-2012 B1

STATIC CONTROL

Life-of-the-carpet static protection

FORMALDEHYDE PURIFICATION

Passes JC/T 1074-2008 Class I

COLOURWAYS

Twelve tones, two expressions

Every colourway shares the same construction and commercial specification. Velura-A offers a softer mottled field; Velura-B introduces a more linear, architectural texture.



Velura-A-1



Velura-A-2



Velura-A-3



Velura-A-4



Velura-A-5



Velura-A-6



Velura-B-1



Velura-B-2



Velura-B-3



Velura-B-4



Velura-B-5



Velura-B-6

COLOUR NOTE

Screen and print colour are indicative only. Request a physical sample before final specification.

IN SITU

Where Velura lands



INSTALLATION

Laying & performance

INSTALLATION METHODS



Quarter turn



Ashlar



Monolithic



Brick

COVERAGE

50 cm x 50 cm modular tiles

ADHESIVE

Project Floors ProjectStik, matched to UltraEco backing

INSTALLED PROFILE

6.0 mm (+/- 0.5 mm) total thickness; 2.5-5.5 mm (+/- 0.5 mm) pile

COMPLIANCE & PERFORMANCE

Velura is tested across flammability, smoke density, static and indoor-air-related performance standards.

TEST	RESULT
Flammability - ASTM E648-17	Class I
Flammability - GB 8624-2012	B1
Smoke density - ASTM E662	< 450
Static propensity - AATCC-134	<= 3.5 kV
Static control	Life-of-the-carpet protection
Formaldehyde purification - JC/T 1074-2008	Class I

UltraEco & product disclosure

Velura pairs a solution-dyed nylon yarn system with UltraEco backing and a modular format. The supplied manufacturer literature also displays recognised product health and environmental disclosure credentials.

- **100% solution-dyed colour**

Colour is integrated into the yarn system.

- **UltraEco backing**

Backing specified in the Velura technical schedule.

- **50 cm x 50 cm modular tile**

Supports targeted maintenance and selective tile replacement.

- **Heavy commercial use**

Specified for sustained commercial interiors.

PUBLISHED CREDENTIALS

The supplied Velura literature displays Ecover, Declare, EPD, CE, and Health Declaration (PHD) marks, together with additional testing credentials. Current certificate scope and validity should be confirmed for the project.



ECOVER & FORMALDEHYDE PURIFICATION

The Velura schedule records formaldehyde purification as passing JC/T 1074-2008 Class I. Ecover branding and related product-health documentation are shown in the manufacturer literature.

IMPORTANT DISCLOSURE NOTE

No recycled-content percentage is stated in the supplied Velura technical schedule.

Dune's 90% recycled-content figure has therefore not been applied to Velura.

Confirm current EPD, Declare and recycled-content documentation with Project Floors before tender or publication.

GET IN TOUCH

Request samples or a project consultation

Velura samples are available for architects, designers and specifiers. Contact Project Floors for samples, current certificates, technical documentation and project support.



PROJECT FLOORS NEW ZEALAND

salesoffice@projectfloors.co.nz

09 444 4565 / projectfloors.co.nz

AUCKLAND STUDIO

55 Barrys Point Road
Takapuna, Auckland 0622

CHRISTCHURCH STUDIO

41 Welles Street
Christchurch Central 8011